

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

AMENDMENTS TO THE SPECIFICATION:

Please replace paragraph [0004] with the following amended paragraph:

[0004] Self-propelled AWP's such as scissor lifts are typically equipped with an apparatus that ~~prevents them from tipping when driven into a pothole or off a curb while the platform is elevated~~ provides additional support for the lift in the event that a wheel is driven into a hole. Such an apparatus works normally by reducing the ground clearance to less than one inch when the platform of the AWP is elevated beyond a certain height.

Please replace paragraph [0007] with the following amended paragraph:

[0007] Current designs are typically based on one of two concepts. A typical six-bar mechanism and a spring are provided to ensure the locking position. This design, however, suffers from excessive numbers of parts and consequently from cost and reliability. A typical four-bar mechanism incorporates a linear actuator linking two of its links. The actuator is either hydraulic or electrical. Drawbacks of this design, however, include ~~cost~~, reliability, and potential leakage of hydraulic fluid.

Please replace paragraph [0022] with the following amended paragraph:

[0022] As noted above, the pothole protection mechanism 20 serves to reduce the ground clearance typically to less than one inch when the platform 16 is elevated beyond a certain height. In this manner, the pothole protection mechanism 20 ~~prevents~~ provides additional support for the vehicle 10 from tipping in the event when a wheel is driven into a pothole or off a curb or the like while the platform 16 is elevated.